



# SAFETY CANS



## SAFETY CANS

For nearly 60 years, our Safety Can product line has been an industry leader of galvanized Type I and Type II Safety Cans that meet OSHA and NFPA Code 30 requirements, and are UL and ULC listed and FM Approved for safe storage and handling of flammable liquids. Eagle offers FM Approved Compliance Solutions in a variety of poly and stainless cans, lab cans, faucet cans, disposal cans, plunger, bench & daub cans, and poly oily waste cans to help keep your personnel and facilities protected. Made in the USA.

### Safety Can options:

- Type I Safety Cans
- Type II Safety Cans
- Type I Poly Cans
- Stainless Cans
- Lab Cans
- Faucet Cans
- DOT Cans
- Disposal Cans
- Specialty Cans
- Plunger Cans
- Bench Cans
- Daub Cans
- Poly Oily Waste Cans
- Biohazardous Cans



Patented comfort grip trigger release plus spring closing lid with nitrile gasket that vents at 5-PSI internal pressure



Double interlock no-weld bottom seam is the only deep drawn seamless can made

## SIMPLY CANTASTIC!

Baked-on Powder Coat Finish + 100 Percent Leak Tested!

Featuring Environmentally Friendly Hot Dipped 24-Gauge Galvanized Steel

Patented Comfort Grip Trigger Release

Spring Closing Lid With Nitrile Gasket That Vents at 5-PSI Internal Pressure

Fixed Handle

Non-Sparking Flame Arrestor and Pour Spout

Baked-on Powder Coat Finish

Available in 1- (3.8 L), 2- (7.6 L), 2.5- (9.5 L) & 5-Gallon (18.9 L) Sizes

Meet OSHA & NFPA Code 30 Requirements

FM, UL & ULC Approved

Accepted Under CARB

Double Interlock No-Weld Bottom Seam



Optional F15 HDPE Funnel Fits Unleaded Fuel Tanks

The Only Deep Drawn Seamless Can Made

Deep Drawn Construction Means No Top or Side Seam

Trilingual Label

Model UI50FS 12½ in. (31.8 cm.) x 13½ in. (34.3 cm.)



FLAMMABLE



DIESEL



KEROSENE



SAFETY CANS



TYPE I SAFETY CANS

|                |                                   |                                  |                                    |                                     |                                      |
|----------------|-----------------------------------|----------------------------------|------------------------------------|-------------------------------------|--------------------------------------|
| FLAMMABLES     |                                   |                                  |                                    |                                     |                                      |
|                |                                   |                                  |                                    |                                     |                                      |
| Model Numbers  | UI4S ⚠                            | UI10S ⚠                          | UI20S ⚠                            | UI25S* ⚠                            | UI50S ⚠                              |
| Model-w/Funnel | UI4FS ⚠                           | UI10FS ⚠                         | UI20FS ⚠                           | UI25FS* ⚠                           | UI50FS ⚠                             |
| Capacity       | 2 qt./2 L                         | 1 gal./3.8 L                     | 2 gal./7.6 L                       | 2½ gal./9.5 L                       | 5 gal./18.9 L                        |
| Dimensions     | 9 in./22.9 cm.<br>5⅝ in./13.5 cm. | 9 in./22.9 cm.<br>8 in./20.4 cm. | 11¼ in./28.6 cm.<br>9 in./24.2 cm. | 11¼ in./28.6 cm.<br>10 in./25.4 cm. | 12½ in./31.8 cm.<br>13½ in./34.3 cm. |
| Weight         | 2.25 lbs./1.1 kg.                 | 3.52 lbs./1.6 kg.                | 5.25 lbs./2.4 kg.                  | 5.7 lbs./2.6 kg.                    | 7 lbs./3.2 kg.                       |
| Construction   | Galvanized                        | Galvanized                       | Galvanized                         | Galvanized                          | Galvanized                           |

TYPE I SAFETY CANS

|                |                                   |                                  |                                    |                                     |                                      |
|----------------|-----------------------------------|----------------------------------|------------------------------------|-------------------------------------|--------------------------------------|
| DIESEL         |                                   |                                  |                                    |                                     |                                      |
|                |                                   |                                  |                                    |                                     |                                      |
| Model Numbers  | UI4SY ⚠                           | UI10SY ⚠                         | UI20SY ⚠                           | UI25SY* ⚠                           | UI50SY ⚠                             |
| Model-w/Funnel | UI4FSY ⚠                          | UI10FSY ⚠                        | UI20FSY ⚠                          | UI25FSY* ⚠                          | UI50FSY ⚠                            |
| Capacity       | 2 qt./2 L                         | 1 gal./3.8 L                     | 2 gal./7.6 L                       | 2½ gal./9.5 L                       | 5 gal./18.9 L                        |
| Dimensions     | 9 in./22.9 cm.<br>5⅝ in./13.5 cm. | 9 in./22.9 cm.<br>8 in./20.4 cm. | 11¼ in./28.6 cm.<br>9 in./24.2 cm. | 11¼ in./28.6 cm.<br>10 in./25.4 cm. | 12½ in./31.8 cm.<br>13½ in./34.3 cm. |
| Weight         | 2.25 lbs./1.1 kg.                 | 3.52 lbs./1.6 kg.                | 5.25 lbs./2.4 kg.                  | 5.7 lbs./2.6 kg.                    | 7 lbs./3.2 kg.                       |
| Construction   | Galvanized                        | Galvanized                       | Galvanized                         | Galvanized                          | Galvanized                           |

Type I Safety Cans

- Eagle Type 1 Safety Cans are constructed of 24-gauge hot dipped galvanized steel, whereas other manufacturers' safety cans use lead-coated terne steel
- These safety cans are accepted under CARB, meet OSHA and NFPA Code 30 requirements, and are UL, ULC and FM Approved for safe handling and storage of gasoline and other flammable liquids
- Available in a variety of colors for the safe handling and storage of kerosene (blue), diesel (yellow) and combustible liquids such as oils (green)

\* Meets the New York City Fire Code Title 29 FC 2204.4.4.1.1  
Maximum 2.5 gallon (9.5 L) container regulations

Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30



TYPE I SAFETY CANS

|                |                                   |                                  |                                    |                                     |                                      |
|----------------|-----------------------------------|----------------------------------|------------------------------------|-------------------------------------|--------------------------------------|
| KEROSENE       |                                   |                                  |                                    |                                     |                                      |
|                |                                   |                                  |                                    |                                     |                                      |
| Model Numbers  | UI4SB ⚠                           | UI10SB ⚠                         | UI20SB ⚠                           | UI25SB* ⚠                           | UI50SB ⚠                             |
| Model-w/Funnel | UI4FSB ⚠                          | UI10FSB ⚠                        | UI20FSB ⚠                          | UI25FSB* ⚠                          | UI50FSB ⚠                            |
| Capacity       | 2 qt./2 L                         | 1 gal./3.8 L                     | 2 gal./7.6 L                       | 2½ gal./9.5 L                       | 5 gal./18.9 L                        |
| Dimensions     | 9 in./22.9 cm.<br>5⅝ in./13.5 cm. | 9 in./22.9 cm.<br>8 in./20.4 cm. | 11¼ in./28.6 cm.<br>9 in./24.2 cm. | 11¼ in./28.6 cm.<br>10 in./25.4 cm. | 12½ in./31.8 cm.<br>13½ in./34.3 cm. |
| Weight         | 2.25 lbs./1.1 kg.                 | 3.52 lbs./1.6 kg.                | 5.25 lbs./2.4 kg.                  | 5.7 lbs./2.6 kg.                    | 7 lbs./3.2 kg.                       |
| Construction   | Galvanized                        | Galvanized                       | Galvanized                         | Galvanized                          | Galvanized                           |

TYPE I SAFETY CANS

|                |                                   |                                  |                                    |                                     |                                      |
|----------------|-----------------------------------|----------------------------------|------------------------------------|-------------------------------------|--------------------------------------|
| COMBUSTIBLES   |                                   |                                  |                                    |                                     |                                      |
|                |                                   |                                  |                                    |                                     |                                      |
| Model Numbers  | UI4SG ⚠                           | UI10SG ⚠                         | UI20SG ⚠                           | UI25SG* ⚠                           | UI50SG ⚠                             |
| Model-w/Funnel | UI4FSG ⚠                          | UI10FSG ⚠                        | UI20FSG ⚠                          | UI25FSG* ⚠                          | UI50FSG ⚠                            |
| Capacity       | 2 qt./2 L                         | 1 gal./3.8 L                     | 2 gal./7.6 L                       | 2½ gal./9.5 L                       | 5 gal./18.9 L                        |
| Dimensions     | 9 in./22.9 cm.<br>5⅝ in./13.5 cm. | 9 in./22.9 cm.<br>8 in./20.4 cm. | 11¼ in./28.6 cm.<br>9 in./24.2 cm. | 11¼ in./28.6 cm.<br>10 in./25.4 cm. | 12½ in./31.8 cm.<br>13½ in./34.3 cm. |
| Weight         | 2.25 lbs./1.1 kg.                 | 3.52 lbs./1.6 kg.                | 5.25 lbs./2.4 kg.                  | 5.7 lbs./2.6 kg.                    | 7 lbs./3.2 kg.                       |
| Construction   | Galvanized                        | Galvanized                       | Galvanized                         | Galvanized                          | Galvanized                           |

TYPE I POLY CANS

TYPE I STAINLESS STEEL CANS









|               |                                   |                                   |                                    |                                   |                                   |                                   |                                    |                                      |
|---------------|-----------------------------------|-----------------------------------|------------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|------------------------------------|--------------------------------------|
|               |                                   |                                   |                                    |                                   |                                   |                                   |                                    |                                      |
| Model Numbers | 14169                             | 14545 ⚠                           | 14261                              | 14561                             | 14535 ⚠                           | 14540 ⚠                           | 1313                               | 1315                                 |
| Capacity      | 1 gal./4 L                        | 5 gal./19 L                       | 2.5 gal./9.5 L                     | 5 gal./19 L                       | 5 gal./19 L                       | 5 gal./19 L                       | 2½ gal./9.5 L                      | 5 gal./19 L                          |
| Dimensions    | 7¼ in./184 mm.<br>11½ in./292 mm. | 11½ in./292 mm.<br>17 in./432 mm. | 10¼ in./273 mm.<br>14¼ in./362 mm. | 12¾ in./324 mm.<br>16 in./406 mm. | 11½ in./292 mm.<br>17 in./432 mm. | 11½ in./292 mm.<br>17 in./432 mm. | 11¼ in./28.6 cm.<br>9 in./24.5 cm. | 11¼ in./28.6 cm.<br>15½ in./39.7 cm. |
| Weight        | 3 lbs./1 kg.                      | 10 lbs./4 kg.                     | 4 lbs./2 kg.                       | 9 lbs./4 kg.                      | 16 lbs./7 kg.                     | 10 lbs./4 kg.                     | 8 lbs./3.7 kg.                     | 10 lbs./4.6 kg.                      |
| Construction  | Poly                              | Poly                              | Poly                               | Poly                              | Poly                              | Poly                              | Stainless                          | Stainless                            |







SAFETY CANS



TYPE II SAFETY CANS

|                  | FLAMMABLES  |   | KEROSENE  |   | DIESEL   |   | COMBUSTIBLES  |   |
|------------------|---|---|---|---|--|---|---|---|
|                  |  |  |  |  |  |  |  |  |
| Model 7/8" Spout | U226S ⚠   | U251S ⚠   | U226SB ⚠  | U251SB ⚠  | U226SY ⚠   | U251SY ⚠  | U226SG ⚠  | U251SG ⚠  |
| Model 5/8" Spout | U226SX5 ⚠   | U251SX5 ⚠   | U226SX5B ⚠  | U251SX5B ⚠  | U226SX5Y ⚠   | U251SX5Y ⚠  | U226SX5G ⚠  | U251SX5G ⚠  |
| Capacity         | 2½ gal./9.5 L   | 5 gal./19 L   | 2½ gal./9.5 L   | 5 gal./19 L   | 2½ gal./9.5 L  | 5 gal./19 L   | 2½ gal./9.5 L   | 5 gal./19 L   |
| Dimensions       | 11¼ in./28.6 cm.<br>9½ in./24.2 cm.   | 12½ in./31.8 cm.<br>15¼ in./40.4 cm.  | 11¼ in./28.6 cm.<br>9½ in./24.2 cm.   | 12½ in./31.8 cm.<br>15¼ in./40.4 cm.  | 11¼ in./28.6 cm.<br>9½ in./24.2 cm.  | 12½ in./31.8 cm.<br>15¼ in./40.4 cm.  | 11¼ in./28.6 cm.<br>9½ in./24.2 cm.   | 12½ in./31.8 cm.<br>15¼ in./40.4 cm.  |
| Weight           | 8 lbs./3.7 kg.  | 10 lbs./4.6 kg.   | 8 lbs./3.7 kg.  | 10 lbs./4.6 kg.   | 8 lbs./3.7 kg.   | 10 lbs./4.6 kg.   | 8 lbs./3.7 kg.  | 10 lbs./4.6 kg.   |
| Construction     | Galvanized  | Galvanized  | Galvanized  | Galvanized  | Galvanized   | Galvanized  | Galvanized  | Galvanized  |

|                  |   |   |  |   |
|------------------|---|---|--|---|
|                  |  |  |  |  |
| Model 7/8" Spout | U211S ⚠   | U211SB ⚠  | U211SY ⚠   | U211SG ⚠  |
| Model 5/8" Spout | U211SX5 ⚠   | U211SX5B ⚠  | U211SX5Y ⚠   | U211SX5G ⚠  |
| Capacity         | 1 gal./3.8 L  | 1 gal./3.8 L  | 1 gal./3.8 L   | 1 gal./3.8 L  |
| Dimensions       | 11¼ in./28.6 cm.<br>7¼ in./18.4 cm.   | 11¼ in./28.6 cm.<br>7¼ in./18.4 cm.   | 11¼ in./28.6 cm.<br>7¼ in./18.4 cm.  | 11¼ in./28.6 cm.<br>7¼ in./18.4 cm.   |
| Weight           | 7 lbs./3.2 kg.  | 7 lbs./3.2 kg.  | 7 lbs./3.2 kg.   | 7 lbs./3.2 kg.  |
| Construction     | Galvanized  | Galvanized  | Galvanized   | Galvanized  |



- Eagle Type II Safety Cans are made of galvanized steel and help reduce the danger of explosion while dispensing flammable liquids through a flexible 12 in. (30.5 cm.) metal spout
- Flame arrestors in filler opening and pour spout

Compliance: OSHA 29 CFR 1910.106, 1926.152 and NFPA Code 30



- Metal Safety Cans are FM, UL and ULC Approved and meet OSHA and NFPA Code 30 requirements. Poly Cans are FM Approved.



STAINLESS



|               |  |
|---------------|--|
| Model Numbers | 1301   |
| Approvals     | FM   |
| Capacity      | 1 gal./3.8 L   |
| Dimensions    | 4¼ in./10.8 cm.<br>8 in./20.4 cm.<br>13 in./33.1 cm. |
| Weight        | 3.75 lbs./1.7 kg.                                    |
| Construction  | Stainless  |



|               |  |
|---------------|--|
| Model Numbers | 12162  |
| Approvals     | FM   |
| Capacity      | 1 gal./4 L   |
| Dimensions    | 4¾ in./117 mm.<br>7 in./194 mm.<br>12¾ in./324 mm. |
| Weight        | 2 lbs./1 kg.                                       |
| Construction  | Poly   |

POLY

|               |   |
|---------------|---|
| Model Numbers | 14065   |
| Approvals     | —   |
| Capacity      | ½ gal./2 L  |
| Dimensions    | 4¾ in./117 mm.<br>7 in./194 mm.<br>9½ in./241 mm. |
| Weight        | 2 lbs./1 kg.                                      |
| Construction  | Poly  |

|               |  |
|---------------|--|
| Model Numbers | 14160  |
| Approvals     | FM   |
| Capacity      | 1 gal./4 L   |
| Dimensions    | 4¾ in./117 mm.<br>7 in./194 mm.<br>12¾ in./324 mm. |
| Weight        | 2 lbs./1 kg.                                       |
| Construction  | Poly   |

FAUCET CANS



|               |                                      |
|---------------|--------------------------------------|
| Model Numbers | 1417 ⚠                               |
| Approvals     | FM                                   |
| Capacity      | 5 gal./19 L                          |
| Dimensions    | 12½ in./31.8 cm.<br>13½ in./34.3 cm. |
| Weight        | 12 lbs./5.5 kg.                      |
| Construction  | Galvanized                           |



|               |                                      |                                    |                                    |                                    |                                    |
|---------------|--------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Model Numbers | 1327                                 | 1215 ⚠                             | 1215SX5 ⚠                          | 1215Y ⚠                            | 1215YSX5 ⚠                         |
| Approvals     | FM                                   | —                                  | —                                  | —                                  | —                                  |
| Capacity      | 5 gal./19 L                          | 5 gal./19 L                        | 5 gal./19 L                        | 5 gal./19 L                        | 5 gal./19 L                        |
| Dimensions    | 11¼ in./28.6 cm.<br>15¼ in./40.4 cm. | 12½ in./31.8 cm.<br>15¾ in./40 cm. | 12½ in./31.8 cm.<br>15¾ in./40 cm. | 12½ in./31.8 cm.<br>15¾ in./40 cm. | 12½ in./31.8 cm.<br>15¾ in./40 cm. |
| Weight        | 9 lbs./4.1 kg.                       | 13 lbs./5.9 kg.                    | 13 lbs./5.9 kg.                    | 13 lbs./5.9 kg.                    | 13 lbs./5.9 kg.                    |
| Construction  | Stainless                            | Galvanized                         | Galvanized                         | Galvanized                         | Galvanized                         |

Laboratory Safety Cans:

- Laboratory Safety Cans reduce the danger of explosions resulting from the ignition of vapors of flammable liquids
- Cans are available in coated metal, stainless steel and high-density polyethylene for safe storage and handling of most chemical compounds

Compliance: OSHA 29 CFR 1910.106, 1925.152 & NFPA Code 30

DOT Transport Type II Safety Cans:

- Reduce the danger of explosion while dispensing flammable liquids through a flexible metal spout
- Have double-walled flame arrestors in filler opening and pour spout
- Heavy duty roll bars protect both spouts, and a thumb screw mechanism assures the filler opening stays closed while being transported














Meet DOT requirements  
Compliance: OSHA 29 CFR 1910.106, 1925.152 & NFPA Code 30 - UN/DOT-1A1/Y1.2/100/08/USA/M4990/0.6mm



SAFETY CANS





















DISPOSAL CANS

|   |   |   |   |  |   |   |
|---|---|---|---|--|---|---|
|  |  |  |  |  |  |  |
| Model Numbers   | 14762   | 14765   | 12751   | 12754  | 14565   | 12772   |
| Approvals   |  |  |  |  |  |  |
| Capacity  | 2 gal./7.5 L  | 5 gal./19 L   | 2 gal./7.5 L  | 5 gal./19 L  | 5 gal./19 L   | 5 gal./19 L   |
| Dimensions  | 12 in./305 mm.<br>14 3/4 in./375 mm.  | 12 in./305 mm.<br>20 in./508 mm.  | 12 in./305 mm.<br>14 3/4 in./375 mm.  | 12 in./305 mm.<br>20 in./508 mm.   | 12 in./305 mm.<br>20 in./508 mm.  | 12 in./305 mm.<br>20 in./508 mm.  |
| Weight  | 7 lbs./3 kg.  | 11 lbs./5 kg.   | 7 lbs./3 kg.  | 11 lbs./5 kg.  | 11 lbs./5 kg.   | 12 lbs./6 kg.   |
| Construction  | Poly  | Poly  | Poly  | Poly   | Poly  | Poly  |



PLUNGER CANS

| METAL   |   |   | POLY  |   |   |
|---|---|---|---|---|---|
|              |              |              |              |              |              |
| <b>P701</b>  | <b>P702</b>  | <b>P704</b>  | <b>P711</b>  | <b>P712</b>  | <b>P714</b>  |
|              |              |              |              |              |              |
| 1 qt./1 L   | 2 qt./1.9 L   | 4 qt./3.8 L   | 1 qt./1 L   | 2 qt./1.9 L   | 4 qt./3.8 L   |
| 6½ in./15.9 cm.<br>8 in./20.4 cm.   | 8 in./20.4 cm.<br>8½ in./21.6 cm.   | 8 in./20.4 cm.<br>10¾ in./27.3 cm.  | 5½ in./13.4 cm.<br>9¾ in./24.8 cm.  | 6½ in./16.6 cm.<br>11 in./28 cm.  | 7¾ in./19.7 cm.<br>13 in./33 cm.  |
| 2.34 lbs./1.1 kg.   | 3 lbs./1.4 kg.  | 3.67 lbs./1.7 kg.   | 2 lbs./0.9 kg.  | 3 lbs./1.4 kg.  | 4 lbs./1.9 kg.  |
| <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Poly</b>   | <b>Poly</b>   | <b>Poly</b>   |















DISPOSAL CANS

|  |  |  |  |   |  |  |
|--|--|--|--|---|--|--|
|  |        |        |        |        |  |  |
| Model Numbers  | 1423  | 1425  | 1323  | 1325  | 605<br>Lift Oil Can  | 211<br>Tallow Pot  |
| Approvals  |       |       |       |       | -  | -  |
| Capacity   | 2 1/2 gal./9.5 L   | 5 gal./19 L  | 2 1/2 gal./9.5 L   | 5 gal./19 L   | 5 gal./19 L  | 4 pt./3.4 L  |
| Dimensions   | 11 1/4 in./28.6 cm.<br>12 in./30.5 cm.   | 11 1/4 in./28.6 cm.<br>18 in./45.8 cm.   | 11 1/4 in./28.6 cm.<br>12 in./30.5 cm.   | 11 1/4 in./28.6 cm.<br>18 in./45.8 cm.  | 11 1/4 in./28.6 cm.<br>38 in./96.6 cm.   | 5 1/4 in./13.3 cm.<br>7 1/2 in./19 cm.   |
| Weight   | 8 lbs./3.7 kg.   | 10 lbs./4.6 kg   | 8 lbs./3.7 kg.   | 10 lbs./4.6 kg.   | 10 lbs./4.6 kg.  | 2 lbs./ .9 kg.   |
| Construction   | Galvanized   | Galvanized   | Stainless  | Stainless   | Galvanized   | Coated Metal   |

SPECIAL CANS



BENCH & DAUB CANS

| DAUB  | BENCH   |   |   |   |   |   |
|---|---|---|---|---|---|---|
|   |   |   |   |   |   |   |
|   |   | Optional cleaning basket shown<br>is available for both models                        |   |   |   |   |
| <b>B600D</b>  | <b>B601</b>   | <b>B602</b>   | <b>B604</b>   | <b>B606</b>   | <b>B606NL</b>   | <b>B608</b>   |
|  |  |  |  |  |  |  |
| ½ pt./0.2 L   | 1 qt./1 L   | 2 qt./1.9 L   | 4 qt./3.8 L   | 6 qt./5.7 L   | 6 qt./5.7 L   | 8 qt./7.6 L   |
| 4¼ in./10.8 cm.<br>3½ in./8.9 cm.   | 6¼ in./15.9 cm.<br>3¾ in./9.2 cm.   | 8 in./20.4 cm.<br>4¼ in./10.8 cm.   | 8 in./20.4 cm.<br>6½ in./16.6 cm.   | 7¾ in./19.7 cm.<br>9½ in./24.2 cm.  | 7¾ in./19.7 cm.<br>9½ in./24.2 cm.  | 11¼ in./28.6 cm.<br>7 in./17.8 cm.  |
| 1 lb./0.5 kg.   | 2.17 lbs./1 kg.   | 3 lbs./1.4 kg.  | 3.5 lbs./1.6 kg.  | 3.67 lbs./1.7 kg.   | 3.67 lbs./1.7 kg.   | 8.25 lbs./3.8 kg.   |
| <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Galvanized</b>   | <b>Galvanized</b>   |

Metal & Polyethelene Disposal Safety Cans:

- Disposal Safety Cans provide an intermediate station for temporary storage of liquid wastes
- Spout cap opens to a wide 80° angle and can be locked open for conveniently emptying various types of containers
- Cans are equipped with a flame arrestor
- Cap assembly opens automatically to relieve excessive internal vapor pressures
- FM Approved



Plunger & Bench Safety Cans:

- Eagle Safety Plunger Cans are ideal for cleaning with flammable or volatile fluids
- Feature flame arrestor dasher screens, brass pump assemblies, and comply with OSHA standards
- When the dasher plate is pushed down, the safety can dispenses a small amount of liquid to easily moisten sponges or rags without messy or dangerous spills
- Polyethylene and coated metal models available
- FM Approved
- Eagle Safety Bench Cans are designed for safer cleaning of small parts or swabbing of larger ones
- Dasher screens act as a fire baffle



SAFETY CANS



POLY WASTE CANS

| Model Numbers | 933FL          | 935FL               | 937FL           | 933FLY          | 935FLY              | 937FLY          |
|---------------|----------------|---------------------|-----------------|-----------------|---------------------|-----------------|
| Approvals     |                |                     |                 |                 |                     |                 |
| Capacity      | 6 gal./22.8 L  | 10 gal./37.9 L      | 14 gal./53 L    | 6 gal./22.8 L   | 10 gal./37.9 L      | 14 gal./53 L    |
| Dimensions    | Width          | 16 1/2 in./42 cm.   | 22 in./55.9 cm. | 22 in./55.9 cm. | 16 1/2 in./42 cm.   | 22 in./55.9 cm. |
|               | Depth          | 13 1/2 in./34.3 cm. | 18 in./45.8 cm. | 18 in./45.8 cm. | 13 1/2 in./34.3 cm. | 18 in./45.8 cm. |
|               | Height         | 16 in./40.7 cm.     | 18 in./45.8 cm. | 21 in./53.4 cm. | 16 in./40.7 cm.     | 21 in./53.4 cm. |
| Weight        | 9 lbs./4.1 kg. | 14 lbs./6.4 kg.     | 16 lbs./7.3 kg. | 9 lbs./4.1 kg.  | 14 lbs./6.4 kg.     | 16 lbs./7.3 kg. |

POLY WASTE CANS

BIOHAZARDOUS POLY WASTE CANS

| Model Numbers | 933FLBK        | 935FLBK             | 937FLBK         | 943BIO          | 945BIO              | 947BIO          |
|---------------|----------------|---------------------|-----------------|-----------------|---------------------|-----------------|
| Approvals     |                |                     |                 |                 |                     |                 |
| Capacity      | 6 gal./22.8 L  | 10 gal./37.9 L      | 14 gal./53 L    | 6 gal./22.8 L   | 10 gal./37.9 L      | 14 gal./53 L    |
| Dimensions    | Width          | 16 1/2 in./42 cm.   | 22 in./55.9 cm. | 22 in./55.9 cm. | 16 1/2 in./42 cm.   | 22 in./55.9 cm. |
|               | Depth          | 13 1/2 in./34.3 cm. | 18 in./45.8 cm. | 18 in./45.8 cm. | 13 1/2 in./34.3 cm. | 18 in./45.8 cm. |
|               | Height         | 16 in./40.7 cm.     | 18 in./45.8 cm. | 21 in./53.4 cm. | 16 in./40.7 cm.     | 21 in./53.4 cm. |
| Weight        | 9 lbs./4.1 kg. | 14 lbs./6.4 kg.     | 16 lbs./7.3 kg. | 9 lbs./4.1 kg.  | 14 lbs./6.4 kg.     | 16 lbs./7.3 kg. |

Polyethylene Oily Waste Cans:

- Fire-safe temporary storage of solvent rags, waste rags, shavings and other materials

Compliance: OSHA 29 CFR 1910.125(e)(4)(ii) and OSHA 29 CFR 1910.125(e)(4)(iii)

Polyethylene Biohazardous Waste Cans:

- Advise workers of potential biohazards and meet OSHA requirements for exposures to blood borne pathogens

Compliance: OSHA 29 CFR 1910.1030

Can be used with or without a liner

Fire-safe temporary storage of solvent rags, waste rags, shavings and other materials subject to spontaneous combustion

Polyethylene construction won't rust or dent and is resistant to most chemical compounds – heavy-wall HDPE construction

Meets OSHA and NFPA Code 30 requirements and are accepted for temporary storage of oily waste materials

Flared base for added stability

Self-closing lid

Molded handles for easy handling

No seam, leakproof construction

Exceeds FM standards for impact, stability & fire testing

Exceeds performance standards at temperatures between -40° F (4.4° C) & 140° F (54.4° C)

Hands-free foot lever

SAFESMOKER™ & Butt Cans

**SAFESMOKER™ Cigarette Receptacle** is made of high-density polyethylene with UV inhibitors, with a galvanized steel collection bucket inside. Design restricts oxygen to quickly extinguish burning butts. Top of container removes easily to access and empty internal bucket. Rain-protective design keeps water out and eliminates odor. Includes integrated hold-down tabs for security and wind protection.

**Eagle Butt Cans** are ideal for “designated smoking areas” inside or outside. Features poly tube and galvanized can base. Yellow for in-plant use and beige for office or commercial areas.

**Original Butt Cans** This all-metal galvanized steel can is excellent for smoking areas in industrial settings. 5-gallon (18.9 L) capacity in yellow or beige.

| Model     | Description       | SafeSmoker™ Cigarette Receptacle Dimensions (dia. x height) | Capacity      | Weight          |
|-----------|-------------------|---|---------------|-----------------|
| 1208BEIGE | SafeSmoker™-Beige | in: 17 1/4 x 43 3/4 cm: 43.8 x 109.9                        | 4 gal./15.2 L | 10 lbs./4.5 kg. |
| 1208BROWN | SafeSmoker™-Brown | in: 17 1/4 x 43 3/4 cm: 43.8 x 109.9                        | 4 gal./15.2 L | 10 lbs./4.5 kg. |
| 1208GRAY  | SafeSmoker™-Gray  | in: 17 1/4 x 43 3/4 cm: 43.8 x 109.9                        | 4 gal./15.2 L | 10 lbs./4.5 kg. |
| 1208BLACK | SafeSmoker™-Black | in: 17 1/4 x 43 3/4 cm: 43.8 x 109.9                        | 4 gal./15.2 L | 10 lbs./4.5 kg. |
| 1206BEIGE | SafeSmoker™-Beige | in: 15 1/4 x 37 3/4 cm: 38.8 x 95.9                         | 5 qt./4.7 L   | 7 lbs./3.2 kg.  |
| 1206BROWN | SafeSmoker™-Brown | in: 15 1/4 x 37 3/4 cm: 38.8 x 95.9                         | 5 qt./4.7 L   | 7 lbs./3.2 kg.  |
| 1206GRAY  | SafeSmoker™-Gray  | in: 15 1/4 x 37 3/4 cm: 38.8 x 95.9                         | 5 qt./4.7 L   | 7 lbs./3.2 kg.  |
| 1206BLACK | SafeSmoker™-Black | in: 15 1/4 x 37 3/4 cm: 38.8 x 95.9                         | 5 qt./4.7 L   | 7 lbs./3.2 kg.  |

| Capacity      | Dimensions                   | Metal/Poly Butt Cans |         |         | Weight         |
|---------------|------------------------------|----------------------|---------|---------|----------------|
| 2 gal./7.58 L | in: 11 x 35 cm: 27.9 x 88.9  | Yellow               | Beige   | Black   | 5 lbs./2.3 kg. |
| 5 gal./18.9 L | in: 12 x 40 cm: 30.5 x 101.6 | 1202                 | 1205BEI | 1205BLK | 7 lbs./3.2 kg. |

| Capacity      | Dimensions                  | Original Butt Can |           | Weight         |
|---------------|-----------------------------|-------------------|-----------|----------------|
| 5 gal./18.9 L | in: 12 x 33 cm: 30.5 x 83.8 | Yellow            | Beige     | 7 lbs./3.2 kg. |
|               |                             | 1200YELLOW        | 1200BEIGE |                |

| Model     | Description               | Decorative SafeSmoker™ Dimensions    | Capacity      | Weight          |
|-----------|---------------------------|--------------------------------------|---------------|-----------------|
| 1212BLACK | SafeSmoker™-Hitching Post | in: 12 1/2 x 44 1/2 cm: 31.8 x 111.8 | 2 gal./7.58 L | 18 lbs./8.2 kg. |
| 1213BLACK | SafeSmoker™-Classic       | in: 12 1/2 x 37 cm: 31.8 x 94        | 2 gal./7.58 L | 18 lbs./8.2 kg. |

SHIPPING SIZES:

|                      | L          | x | W      | x | H    |
|----------------------|------------|---|--------|---|------|
| 1200                 | in: 13     | x | 13     | x | 20   |
|                      | cm: 33.1   | x | 33.1   | x | 50.8 |
| 1202                 | in: 13     | x | 13     | x | 28   |
|                      | cm: 33.1   | x | 33.1   | x | 71.2 |
| 1205                 | in: 13     | x | 13     | x | 28   |
|                      | cm: 33.1   | x | 33.1   | x | 71.2 |
| 1206                 | in: 16     | x | 16     | x | 21   |
|                      | cm: 40.7   | x | 40.7   | x | 53.4 |
| 1208                 | in: 17 1/2 | x | 17 1/2 | x | 25   |
|                      | cm: 44.5   | x | 44.5   | x | 63.5 |
| All are shipped UPS. |            |   |        |   |      |

Container top removes easily to empty internal galvanized steel bucket.



1200BEIGE

1200YELLOW

1202BLACK

1202BEIGE

1202YELLOW

1205BLACK

1205BEIGE

1205YELLOW